



CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

Control Panel Systems Ontario Ltd.
1712 Baseline Road West
Courtice, Ontario L1E 2S8 Canada

Fulfills the requirements of

ISO/IEC 17025:2017

In the field of

CALIBRATION

This certificate is valid only when accompanied by a current scope of accreditation document.
The current scope of accreditation can be verified at www.anab.org.

Jason Stine, Vice President

Expiry Date: 15 July 2028
Certificate Number: L2122-1



This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory
quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

Control Panel Systems Ontario Ltd.

1712 Baseline Road West
Courtice, Ontario L1E 2S8 Canada
Todd Delisle 905-668-8100 / 905-438-8521

CALIBRATION

ISO/IEC 17025 Accreditation Granted: **07 July 2026**

Certificate Number: **L2122-1** Certificate Expiry Date: **15 July 2028**


Mass and Mass Related

Parameter/Equipment	Range	Expanded Uncertainty of Measurement (+/-)	Reference Standard, Method, and/or Equipment
Torque Transducers ¹	(2 to 20) N·m (15 to 75) N·m (32 to 180) N·m (100 to 500) N·m	0.2 % of reading 0.18 % of reading 0.18 % of reading 0.18 % of reading	Comparison to Master Weights, Calibration Beams
Torque Power Tools	(0.2 to 1) N·m (0.5 to 5) N·m (2 to 20) N·m (7.5 to 75) N·m (18 to 180) N·m (50 to 500) N·m	0.005 N·m 0.07 N·m 0.46 N·m 0.6 N·m 1.6 N·m 2.2 N·m	Comparison to Torque Transducers
Torque Wrenches	(0.5 to 5) N·m (2 to 20) N·m (7.5 to 75) N·m (18 to 180) N·m (50 to 500) N·m (280 to 1 400) N·m	0.3 N·m 0.6 N·m 2.4 N·m 2.9 N·m 5.8 N·m 5.8 N·m	Comparison to Torque Transducers

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 ($k=2$), corresponding to a confidence level of approximately 95%.

Notes:

1. Uncertainties do not include type A contributors from a "best existing device".
2. Unless otherwise listed in the far-right column, the calibration procedure utilized by the laboratory was internally developed.



Jason Stine, Vice President

This Scope of Accreditation, version 009, was last updated on: 07 July 2026 and is valid only when accompanied by the Certificate.

Page 1 of 1

1899 L Street NW, Suite 1100-A, Washington, DC 20036

414-501-5494

www.anab.org